

FRAME ANALYSIS OF REINFORCED CONCRETE SHEAR WALLS WITH
OPENINGS

NORLIZAN BINTI WAHID

Master of Engineering (Civil – Structure)

Faculty of Civil Engineering
Universiti Teknologi Malaysia

APRIL, 2007

UNIVERSITI TEKNOLOGI MALAYSIA

BORANG PENGESAHAN STATUS TESIS*

JUDUL: FRAME ANALYSIS OF REINFORCED CONCRETE SHEAR WALLS WITH OPENINGS

SESI PENGAJIAN: 2006/2007

Saya NORLIZAN BINTI WAHID
(HURUF BESAR)

mengaku membenarkan tesis (~~PSM/Sarjana/Doktor Falsafah~~)* ini disimpan di Perpustakaan Universiti Teknologi Malaysia dengan syarat-syarat kegunaan seperti berikut:

1. Tesis adalah hakmilik Universiti Teknologi Malaysia.
2. Perpustakaan Universiti Teknologi Malaysia dibenarkan membuat salinan untuk tujuan pengajian sahaja.
3. Perpustakaan dibenarkan membuat salinan tesis ini sebagai bahan pertukaran antara institusi pengajian tinggi.
4. **Sila tandakan (✓)

SULIT (Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia seperti yang termaktub di dalam AKTA RAHSIA RASMI 1972)

TERHAD (Mengandungi maklumat TERHAD yang telah ditentukan oleh organisasi/badan di mana penyelidikan dijalankan)

TIDAK TERHAD

Disahkan oleh



(TANDATANGAN PENULIS)



(TANDATANGAN PENYELIA)

Alamat Tetap: NO 62, JLN KESUMA 5/12D
BANDAR TASIK KESUMA
43700 BERANANG
SELANGOR


P.M. DR. ABDUL KADIR MARSONO
(Nama Penyelia)

Tarikh : 25 APRIL 2007

Tarikh : 25 APRIL 2007

- CATATAN:
- * Potong yang tidak berkenaan.
 - ** Jika tesis ini SULIT atau TERHAD, sila lampirkan surat daripada pihak berkuasa/organisasi berkenaan dengan menyatakan sekali sebab dan tempoh tesis ini perlu dikelaskan sebagai SULIT atau TERHAD.
 - ♦ Tesis dimaksudkan sebagai tesis bagi Ijazah Doktor Falsafah dan Sarjana secara penyelidikan, atau disertasi bagi pengajian secara kerja kursus dan penyelidikan, atau Laporan Projek Sarjana Muda (PSM).


I declare that this project report entitled “*Frame Analysis Of Reinforced Concrete Shear Walls With Openings*” is the result of my own research except as cited in the references. The report has not been accepted for any degree and is not concurrently submitted in candidature of any other degree.

Signature : 

Name : **NORLIZAN BINTI WAHID**

Date : **25 APRIL 2007**

“I declare that I have read through this project report and to my opinion this report is adequate in term of scope and quality for the purpose of awarding the degree of Master of Engineering (Civil-Structure)

Signature : 

Name of Supervisor : **ASSOC. PROF. DR. ABDUL KADIR MARSONO**

Date : **25 APRIL 2007**

ACKNOWLEDGEMENT

I wish to express my sincere appreciation to my project supervisor, Assoc. Prof. Dr. Abdul Kadir Marsono, for encouragement, guidance and constructive criticisms. Without his support, the project would not have been the same as presented here.

I am indebted to all the lecturers that had been taught me and their guidance in the process of gaining knowledge in this field. My sincere appreciation also extends to all my colleagues and others who have provided assistance at various occasions. Their views and tips are making life useful.

Finally, thanks to my husband, my mother and all the family members for their understanding and encouragement.

ABSTRACT

There are several types of analysis methods available for analysing shear walls of the building structures. Frame analyses is one of the methods, and were used in this study to determine the ultimate strength of reinforced concrete coupled shear wall structures and its structural behaviour under lateral loading. Multiframe Version 5.16 software which based on linear (first-order elastic) analysis method were used to analyse the shear wall models adopted from previous research. Results show that linear elastic of frame analysis method was overestimating the ultimate strength of shear wall models and not reliable enough for this analysis compared to analytical Continuous Connection Method (CCM) and Non-Linear Finite Element Analysis (NLFEA) method. The difference was about four times higher than the experimental results being conducted by the previous researcher. However the structural behaviour of walls and its coupling beam at ultimate condition was still pose similar behaviour to the observation made on the experimental test and Non-Linear Finite Element Analysis (NLFEA).

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENTS	iv
	ABSTRAK	v
	ABSTRACT	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xi
	LIST OF SYMBOLS	xiii
	LIST OF APPENDICES	xiv
1	INTRODUCTION	1
	1.1 Analysis of Shear Walls	2
	1.2 Previous Work	3
	1.3 Objectives	3
	1.4 Scope of Project	4
2	LITERATURE REVIEW	5
	2.1 Shear Wall Systems	5
	2.1.1 Coupled Shear Walls	6
	2.1.2 Modes of Failure for Shear Wall	8
	2.2 Coupling Beams	9
	2.2.1 Flexural mode of failure	10
	2.2.2 Pure Shear Mode of Failure	11

2.2.3	Flexure plus Shear Mode of Failure	13
2.3	Method of Analysis of Shear Wall Structures	14
2.3.1	Finite Element Analysis (FEA)	15
2.3.2	Continuous Connection Method (CCM)	16
2.3.4	Equivalent Frame Analysis	17
2.4	Multiframe Version 5.16	18
2.4.1	Methods and Conventions Used in Multiframe Version 5.16	19
2.5	The Shear Wall Models	23
3	RESEARCH METHODOLOGY	26
3.1	Introduction	26
3.2	Modelling and Analysing the Shear Wall Models	27
3.2.1	Installing the Section Properties	27
3.2.2	Building the Frame Models in Multiframe	39
3.2.3	Loading	42
3.2.4	Analysing the Shear Wall Models	43
3.3	Results Interpretation	44
4	DATA COLLECTION AND ANALYSIS	46
4.1	Ultimate Load Condition	46
4.2	Deflections	47
4.3	Stresses	53
4.3.1	Resultant Stress	56
4.3.2	Shear Stress	59
5	DISCUSSION OF RESULTS	61
5.1	Load Displacement Characteristic	61
5.2	Mode of Failure	66
5.3	Concrete Crushed and Crack Observations	67
6	CONCLUSIONS AND RECOMMENDATIONS	71
6.1	Conclusions	71
6.2	Recommendations	74

REFERENCES	75
-------------------	----

APPENDICES

A	Joint Displacements At Ultimate Load	77
B	Results From Previous Research	
	By Marsono (2000)	90

CHAPTER 1

INTRODUCTION

High rise building is a structure vertically cantilevered from the ground level subjected to axial loading and lateral forces. It consists of frames, beams, shear walls, core walls, and slab structures which interact through their connected edges to distribute lateral and axial load imposed to the building. Lateral forces generated either due to wind blowing against the building or due to the inertia forces induced by ground shaking which tend to snap the building in shear and push it over in bending. These types of forces can be resisted by the use of shear wall system which is one of the most efficient methods of ensuring the lateral stability of tall buildings.

For building taller than 10-stories, frame action obtained by the interaction of slabs and columns is not adequate to give the required lateral stiffness (Taranath 1998). It also has become an uneconomical solution for tall buildings. However it can be improved by strategically placing shear walls as it very effective in maintaining the lateral stability of tall buildings under severe wind or earthquake loading.

Coupled shear wall is a continuous wall with vertical rows of opening created for windows and doors, coupled by beams that interconnecting the wall piers across the openings. These connecting beams are referred to as coupling beams. It may be

shallow or deep beam type constrained by the walls on either side. Coupling beam has to be ensured adequately strong and stiff under elastic loading, ductile and able to dissipate energy under inelastic loading to achieve desirable performance of these structures (Lam et al., 2005) as its behaviour and modes of failure are highly effect the mode of failure of shear wall.

1.1 Analysis of Shear Walls

There are several types of analysis methods available for analysing shear walls structure. The analysis can be made in elastic, elasto-plastic and ultimate condition. However, due to uncertain and in-ability to analyse and interpret the post elastic behaviour or possibly time constraint, the elastic method is preferred for its simplicity. This elastic method of analysis consists of Continuous Connection Method (CCM), Transfer Matrix Method, Wide Column Analogy (WCA) or frame analysis, Finite Element Method and Discrete Force Method.

The Non-Linear Finite Element Analysis (NLFEA) can achieve excellent agreement with the test results (Driver et al., 1998). But this method is time consuming where relatively simple force distribution output is required. Frame analysis method offers the advantage of being simple and relatively accurate yet the results output are still acceptable by engineers. Thus, this study was carried out on shear wall structures adopted from research models by Marsono (2000) using frame analysis based software, to evaluate the accuracy of the methods.

1.2 Previous Work

Previous researcher, Marsono (2000) has conducted an experimental work on small scaled model of various types of shear walls structure. Results from the experiment in the form of stresses and strains, crack distributions and ultimate strength then used to establish the analytical method (Continuous Connection Method, CCM) of analysis. The non-linear finite element analysis (NLFEA) was performed as a tool to affirm the experimental results and the analytical mode of failure and ultimate strength predictions. The experimental and NLFEA results were in very close agreement in predicting the ultimate strength and mode of failure of coupled shear wall structure.

1.3 Objectives

The main objectives of the research are as follows:

- a) To carry out a frame analysis on shear wall models using Multiframe Version 5.16 software.
- b) To check the reliability of frame analysis method compared to analytical Continuous Connection Method (CCM) and Non-Linear Finite Element Analysis (NLFEA) method.
- c) To approximately determine the crack formation and crushing of concrete at shear wall referring to the results obtained from the frame analysis.

1.4 Scope of Project

Analysis was carried out on a scaled model of shear walls adopted from Model Number 5 & 6 of PhD research by Marsono (2000) and no design work on the structure involved. The software used to analyse the models was Mutiframe version 5.16 which based on linear elastic method of frame analysis. All the material properties assigned and load applied were also taken from the previous research. Results obtained from the analysis then being compared to experimental study, analytical CCM and NLFEA results obtained from previous research.